

XJ1000-XX Series Attenuator

FEATURES

- Metal housing, nickel plated.
- Connectors: 75 ohm, IEC 169-2(m) to IEC 169-2(f).



Attenuator

XJ1000

SPECIFICATIONS

Item	XJ1000
Frequency (MHz)	5-1000
Attenuation Value (dB)	1,2,3,4,5,6,7,8,9,10,11,12,13,14,15,16,17,18,19,20 optional
1Tolerance (dB)	± 1.0
Return Loss (dB)	≥ 18
Impedance (Ω)	75

XG2000 Overvoltage Suppressor

FEATURES

- Metal housing, nickel plated.
- Connectors: 75 ohm, IEC 169-2(m) to IEC 169-2(f).



Overvoltage Suppressor

XG2000

SPECIFICATIONS

Item	XG2000
Nominal Voltage	230±42V DC
Residual Voltage (100V/uS)	< 800V
Nominal Discharge Current	75KV
Frequency	5-1000MHz
Insertion Loss (dB)	≤0.5dB
Return Loss	≥18dB
Isolation Resistance	≥1000MΩ

XG4000-XX Series High Pass Filter

FEATURES

- Metal housing, nickel plated.
- Connectors: 75 ohm, IEC 169-2(m) to IEC 169-2(f).



High Pass Filter

XG4000

SPECIFICATIONS

Model	Pass Band (MHz)	Through (dB)	Stop Band (MHz)	Rejection (dB)	Return Loss (dB)
XG4000-47	47-1000	≤1.0	5-30	≥46	≥18
XG4000-54	54-1000	≤1.0	5-40	≥46	≥18
XG4000-85	85-1000	≤1.0	5-65	≥46	≥18